


# GNC-0105T, Gigabit PCI Network Card, 1 x RJ45

## Product Images

---



## Short Description

---

- 10/100/1000Mbps wire speed transmission and reception
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Built-in Wake-on-LAN feature to startup computers remotely
- Supports most network operating systems (NOS)
- Supports 32 bit PCI 1.0 and PCI 2.2 bus
  - 10/100/1000Mbps wire speed transmission and reception
  - IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
  - Built-in Wake-on-LAN feature to startup computers remotely
  - Supports most network operating systems (NOS)
  - Supports 32 bit PCI 1.0 and PCI 2.2 bus

## Description

---

### **Product overview**

The LevelOne GNC-0105T is a 32-bit Gigabit Ethernet PCI adapter for desktop computers. It supports 1000Mbps half-duplex and 2000Mbps full-duplex data traffic for Windows 98SE / ME / 2000 / XP and Vista-based operating systems.

### **Gigabit PCI adapter**

The Gigabit GNC-0105T PCI adapter is plug-and-play capable and does not require any additional software installation. It supports 802.1Q prioritization for optimized data traffic and offers Auto-MDI / MDI-X on the RJ-45 LAN port. The LED display shows network connection, link speed and activity. The GNC-0105T complies with the FCC, CE standards.

## Additional Information

---

Gigabit RJ45	1
Color	Green
EAN	4015867224175
Model Number	GNC-0105T
Features	Data rate 10/100/1000 Mbps (Auto-Negotiation capability), Support ACPI and PCI power management, Automatic crossover support for crossover or regular cable
Data rate	Gigabit Ethernet
Host Interface	PCI
Network Card Type	Wired
Approval and Compliance	CE, FCC, RoHS
Operating humidity	10% RH ~ 90% RH
Operating temperature	0°C ~ 55°C
Compatible operating systems	Windows XP / ME / Server 2000 / Server 2003 / Server 2008 / Vista / Win 7 / Win 8 / Win 8.1 / Win 10 32&64Bit
Storage humidity	0% RH ~ 90% RH
Storage temperature	-40°C ~ 70°C
Package Contents	GNC-0105T Quick Installation Guide Ressource CD (Bedienungsanleitung, Treiber) Flache Halterung
Dimensions (W x D x H)	58 x 117 x 16 mm
Product weight (kg)	0.0478
Jumbo frame (KB)	9
Standards	IEEE 802.3z, IEEE 802.3, IEEE 802.1Q VLANs, IEEE 802.3x, IEEE 1588, IEEE 802.3az - Energy Efficient Ethernet (EEE)

